

UA10 Thin Client

Seamless Connectivity,
Precision Productivity



Smart Performance, Smarter Savings

The UA10, powered by Intel® Celeron® Processor, combines energy efficiency with reliable performance, helping businesses maximize output while minimizing electricity expenses.



Work Smarter, Interact Better

Dual multi-display support, a 5M webcam, and dual microphones ensure efficient functionality and clear communication for healthcare, finance, and public sectors



See More, Achieve More

Featuring a 23.8" FHD LCD in a bezel-free, ultra-thin design, the UA10 minimizes distractions, letting you dive into work with clarity and focus



Adaptable Angles for Total Comfort

Work your way with UA10's adjustable orientations, supporting up to 90-degree portrait and landscape modes to maximize comfort in any task

UA10 Thin Client

Seamless Connectivity, Precision Productivity



Performance

CPU	Intel® Jasper Lake N5100 processor supports up to 2.8GHz Burst frequency, Quad Core
Memory	8GB DDR4-2933MHz single channel
Multiple Display	23.8" full HD LCD, 1 DP 1.4, 1 DVI-D
Display Resolution	Full HD on LCD, 4K 60Hz on connected display (Max)
Brightness (typical)	250 cd/m ² typ.
Viewing Angle	CR(>10):178/178 (V/H) typ.
Graphic & Multimedia	<ul style="list-style-type: none"> Intel® 11th UHD Graphics 24EUs Full HD 5MP webcam with microphones HEVC, VP9, and AVC decode support

Expandability

WiFi (Optional)	<ul style="list-style-type: none"> M.2 for WiFi module (E Key) 2 external antenna holes reserved Bluetooth 5.3
Storage	<ul style="list-style-type: none"> Onboard 8GB eMMC as default mSATA slot for SSD installation
LAN	RJ-45 10/100/1000Mbps
USB	2 USB-A 2.0, 2 USB-A 3.2 Gen1
Audio & Sound	Combo audio jack for headset & internal speakers
Power	DC 19V/ 3.42A 65W power adapter
Mechanical Function	Tilt: -5°~23° Pivot: 90° Height Adjust: 110 mm Swivel: -65/65°

Security / Manageability

Security Lock	Security lock 3*7mm
WoL	RJ45 LAN with standby power design supports Magic Packet wake-up event
TPM	fTPM 2.0

Environment

Cooling	Passive cooling (Noise-Free)
Operating Temperature	0 °C to 35 °C, 32 °F to 95 °F
Operating Humidity	20% - 80% non-condensing

Physical

Dimension (w x h x d) & Weight:
 540 x 433 x 48mm (without foot stand) / 3.2Kg
 540 x 520 x 249mm (with foot stand) / 5.6Kg

Note: UltraArmor retains the authority to modify, correct, cancel, and/or enhance information, as well as products and programs described in such information, at any time without prior notice.