

UA2 Thin Client

Redefining the office Workspace



IGEL

Ready

**5 YEARS
WARRANTY**



"Say goodbye to clutter and hello to simplicity with the UA2—Designed for industries that demand precision and style, such as finance, healthcare, and retail."



Power in the Palm of Your Hand

UA2's palm-sized design delivers robust office solutions, enabling Unified Communication for seamless calls, meetings, and messaging—all within your grasp



Big on Savings, Small on Energy

Powered by the Intel Alder Lake, UA2's fanless design consumes just 7 watts per hour—8x more efficient than traditional PCs



One Cable, Endless Possibilities

Multitask effortlessly, even in tight spaces. UA2 simplifies your workspace with a single USB Type-C cable, handling data storage, power delivery, audio, and video



Work Clean, Work Efficiently

Designed for industries that require clutter-free environments, such as finance, healthcare, and retail sectors. Enjoy a organized workspace without sacrificing top-tier performance

UA2 Thin Client

Redefining the office Workspace



Performance

CPU	Intel® Alder Lake N100 processor supports up to 3.4GHz max turbo boost, Quad Core
Memory	8GB DDR4-3200MHz single channel (up to 16GB optional)
Multiple Display	2 DP 1.4 and 1 USB-C DP Alt mode <ul style="list-style-type: none"> Up to 1 x 4K60 + 2 x 1080P concurrent Up to 2 x 4K60 HDR
Display Resolution	4K 60Hz (Max)
Graphic & Multimedia	<ul style="list-style-type: none"> Intel® 12th UHD Graphics 24EUs HEVC, VP9, and AVC decode support Support AVX2 instruction sets

Expandability

WiFi (Optional)	<ul style="list-style-type: none"> M.2 for WiFi module (E Key) 2 external antenna holes reserved Bluetooth 5.3
Storage	<ul style="list-style-type: none"> Onboard 16GB eMMC as default (up to 64GB optional) mSATA slot for SSD installation
LAN	RJ-45 10/100/1000Mbps
USB	4 USB-A 2.0, 2 USB-A 3.2 Gen1, 1 USB-C 3.2 Gen2 with DP Alt Mode, power delivery, data storage
Audio & Sound	Combo audio jack for headset & internal speaker
Power	DC 12V/ 4A 48W power adapter

Security / Manageability

Processor Security	Intel® boot guard
Security Lock	Security lock 3*7mm
WoL	RJ45 LAN with standby power design supports Magic Packet wake-up event
TPM	Infineon TPM 2.0

Environment

Cooling	Passive cooling (Noise-Free)
Operating Temperature	0 °C to 35 °C, 32 °F to 95 °F in vertical position
Operating Humidity	20% - 80% non-condensing
ECO design	30% Post-consumer recycled plastic (PCR) for plastic chassis

Physical

- Dimension (w x h x d) & Weight
- 37 x 186 x 157mm (without foot stand) / 0.9Kg
 - 57 x 191.5 x 157mm (with foot stand) / 0.94Kg

Note: UltraArmor may update or modify information, products, or programs without prior notice.