



UA10 Features



Plug-and-Play Efficiency

UA10, powered by Intel® Smart Display Module-Large, streamlines thin-client solutions with easy deployment, diverse functions, and cost efficiency



Enhance Visuals with 2 Multi-display

Tailored for healthcare, finance, and public sectors, UA10 supports dual multi-displays with DP and DVI-D ports, enhancing workplace functionality



Built-in 5MP webcam, dual microphones

UA10 facilitates easy collaboration with a 5M webcam and dual microphones for seamless online interaction at home or in the office



Bezel-less, Ultra-thin Design

Dive into work details with a 23.8" FHD LCD bezel-free, ultra-thin design for maximum concentration



Ultimate Efficiency at Any Angle

Maximize comfort with UA10's versatile up to 90-degree portrait and landscape orientations for distraction-free efficiency



Energy-efficiency CPUs

Save on electricity bills with UA10's Intel® Celeron® Jasper Lake N5100, meeting tight corporate budgets efficiently

UA10 TC238-JL

Performance

CPU	Intel® Jasper Lake N5100 processor supports up to 2.8GHz Burst frequency, Quad Core four threads
Memory	4GB DDR4-2933MHz single channel
Multiple Display	23.8" full HD LCD, 1 DP 1.4, 1 DVI-D
Display Resolution	Full HD on LCD, 4K 60Hz on connected displays (Max)
Brightness (typical)	250 cd/m ² typ.
Viewing Angle	CR(>10):178/178 (V/H) typ.
Graphic & Multimedia	<ul style="list-style-type: none"> Intel® 11th UHD Graphics 24EUs Full HD 5MP webcam with microphones HEVC, VP9, and AVC decode support

Expandability

WiFi (Optional)	<ul style="list-style-type: none"> M.2 for WiFi module (E Key) 2 external antenna holes reserved Bluetooth 5.3
Storage	<ul style="list-style-type: none"> Onboard 8GB eMMC as default mSATA slot for SSD installation
LAN	RJ-45 10/100/1000Mbps
USB	2 USB-A 2.0, 2 USB-A 3.2 Gen1
Audio	Combo audio jack for headset & internal speakers
Power	DC 19V/ 3.42A 65W power adapter
Mechanical Function	Tilt: -5°~23° Pivot (None): 90° Height Adjust (None): 110 mm Swivel (None): -65/65°

Security / Manageability

Security Lock	Kensington lock slot
WoL	RJ45 LAN with standby power design supports Magic Packet wake-up event
TPM	fTPM 2.0

Environment

Cooling	Passive cooling (Noise-Free)
Operating Temperature	0 °C to 35 °C, 32 °F to 95 °F
Operating Humidity	20% - 80% non-condensing

Physical

Dimension (w x h x d) & Weight:

- 540 x 433 x 48mm (without foot stand) / 3.2Kg
- 540 x 520 x 249mm (with foot stand) / 5.6Kg

Warranty Policy:

5-year limited warranty, excluding components*

* For detailed warranty policy, refer to UltrArmor's official website FAQ page

Note: UltrArmor retains the authority to modify, correct, cancel, and/or enhance information, as well as products and programs described in such information, at any time without prior notice.